🚀 **A step-by-step guide to creating a load-balanced architecture using VirtualBox, Ubuntu 24.04 LTS, HAProxy, and Nginx. Perfect for students, developers, or home lab enthusiasts.**

Part 1: Install VirtualBox on Ubuntu

🔹 **Step 1: Update Your System**

```
sudo apt update && sudo apt upgrade -y
```

🔹 **Step 2: Install Required Dependencies**

```
sudo apt install -y dkms build-essential linux-headers-$(uname -r)
```

🔹 **Step 3: Add Oracle VirtualBox Repository**

🔑 **Add GPG Key**

```
wget -q https://www.virtualbox.org/download/oracle_vbox_2016.asc -O- | \
sudo gpg --dearmor -o /usr/share/keyrings/oracle-virtualbox.gpg
```

📦 **Add Repository**

```
echo "deb [signed-by=/usr/share/keyrings/oracle-virtualbox.gpg] https://download.virtualbox.org/virtualbox/debian $(lsb_release -cs) contrib" | \
sudo tee /etc/apt/sources.list.d/virtualbox.list
```

🔁 **Update Package Index**

```
sudo apt update
```

🔹 **Step 4: Install VirtualBox**

```
sudo apt install virtualbox-7.0 -y
```

💡 Replace 7.0 with another version (like 6.1) if needed.

🔹 **Step 5 (Optional): Install Extension Pack**

Download from 👉 https://www.virtualbox.org/wiki/Downloads
Then install:

```
sudo VBoxManage extpack install Oracle_VM_VirtualBox_Extension_Pack-*.vbox-extpack
```

🔹 **Step 6: Launch VirtualBox**

```
virtualbox
```

Or via GUI: **Activities Menu → Oracle VM VirtualBox**

📌 **Check Installed Version**

```
VBoxManage --version
```

Expected output:

```
7.0.18r162988
```

🌐 Part 2: Ubuntu 24.04 LTS VM Setup (VirtualBox)

🖥️ VM Settings

- **Format**: VDI
- **Storage**: Dynamically allocated
- **Disk Size**: 20 GB
- **RAM**: ≥ 2 GB
- **Adapter 1**: Bridged Adapter (internet)
- **Adapter 2**: Host-only Adapter (vboxnet0)

🧱 Install Ubuntu

1. Download ISO from ubuntu.com.
2. Mount ISO via VirtualBox Storage → Optical Drive.
3. Start VM and install Ubuntu:
    - Set hostname (web1, web2, loadbalancer)
    - Create a user and strong password

⚙️ Part 3: Post-Installation Setup

```
sudo apt update && sudo apt upgrade -y

timedatectl set-ntp true
```

🌐 Part 4: Configure Network (Netplan)

🔍 Get Your Gateway

On host OS :

```
ip route | grep default
```

Example output:

```
default via 10.X.X.XX dev wlp3s0
```

📝 Configure /etc/netplan/01-netcfg.yaml (e.g. for web1, replace XX with the last part of the IP: web1 → 11, web2 → 12, loadbalancer → 10, etc.)

```
network:
 version: 2
 ethernets:
  enp0s3:
   dhcp4: no
   addresses: [10.X.X.50/24]
   routes:
    - to: 0.0.0.0/0
      via: 10.X.X.XX
   nameservers:
    addresses: [8.8.8.8, 1.1.1.1]

  enp0s8:
   dhcp4: no
   addresses: [192.168.56.XX/24]
```

⚠ Don't add gateway4 to enp0s8.

*** Please use 2 SPACES per level where needed, no TABs**

Apply Changes

```
sudo chmod 644 /etc/netplan/01-netcfg.yaml
sudo netplan apply
```

Verify

```
ip a
ping 8.8.8.8
curl https://google.com
```

🖊️ Part 5: Edit /etc/hosts on All VMs

```
sudo nano /etc/hosts
```

Add:

```
192.168.56.10 loadbalancer
192.168.56.11 web1
192.168.56.12 web2
192.168.56.13 web3
```

⚖️ Part 6: HAProxy Load Balancer (on loadbalancer VM)

Install HAProxy

```
sudo apt update
sudo apt install haproxy -y
sudo systemctl enable haproxy
sudo cp /etc/haproxy/haproxy.cfg /etc/haproxy/haproxy.cfg.backup
sudo nano /etc/haproxy/haproxy.cfg
```

HAProxy Config:

(in the Next page 😊 😟)

```
global
    log /dev/log local0
    log /dev/log local1 notice
    daemon

defaults
    log    global
    mode    http
    option  httplog
    option  dontlognull
    timeout connect 5000
    timeout client  50000
    timeout server  50000

frontend http_front
    bind *:80
    default_backend http_back

backend http_back
    balance roundrobin
    server web1 192.168.56.11:80 check
    server web2 192.168.56.12:80 check
    server web3 192.168.56.13:80 check

listen stats
    bind *:8080
    stats enable
    stats uri /stats
    stats refresh 10s
    stats admin if TRUE
```

Test & Start HAProxy

```
sudo haproxy -c -f /etc/haproxy/haproxy.cfg

sudo systemctl restart haproxy

sudo systemctl status haproxy
```

🌎 Part 7: Web Servers (web1, web2, web3)

Install Nginx

```
sudo apt update

sudo apt install nginx -y

sudo systemctl enable nginx

sudo systemctl start nginx
```

Create Web Pages

#On Web 1

```
echo "<h1>Welcome from Web Server 1</h1><p>Server IP: 192.168.56.11</p>" | sudo tee /var/www/html/index.html
```

#On Web 2

```
echo "<h1>Welcome from Web Server 2</h1><p>Server IP: 192.168.56.12</p>" | sudo tee /var/www/html/index.html
```

#On Web 3

```
echo "<h1>Welcome from Web Server 3</h1><p>Server IP: 192.168.56.13</p>" | sudo tee /var/www/html/index.html
```

🔥 Part 8: Configure UFW (Firewall)

```
sudo ufw allow 'Nginx Full'
sudo ufw enable
```

🧪 Part 9: Testing & Verification

Test Load Balancing

```
for i in {1..10}; do curl http://192.168.56.10; echo "---"; done
```

Browser Testing (on Host)

Then visit:

- http://loadbalancer.local
- http://192.168.56.10:8080/stats

📊 Part 10: Logs & Monitoring

HAProxy Logs

```
sudo tail -f /var/log/haproxy.log
```

Nginx Logs

```
sudo tail -f /var/log/nginx/access.log
sudo tail -f /var/log/nginx/error.log
```

✅ Final Notes

- This setup is a great foundation to learn load balancing and server management.
- You can expand it by adding Node.js apps, databases, or Docker.
- Feel free to test this setup on real hardware (e.g., Raspberry Pi or old PCs).
- Customize and build on top of this for your own projects or portfolio!

🙌 Thanks for Reading

If this helped you, consider sharing it with others.
Made with 💻 by **[Rishabh Aka Raiplus]**

Bhind, Madhya Pradesh, India |
|rishabhsinghrajawat.dev@gmail.com||[https://github.com/Raiplus] ||
||[https://www.linkedin.com/in/rishabh-singh-rajawat-5a1b782bb/]|